

CAD/CAM – SYSTEMEN

- TopSolid
- WinTool (gereedschapsbeheer)

CNC FREES/DRAAICOMBINATIE

	Diameter [mm]	Verplaatsing (x,y,z) [mm]
SHW UniSpeed 5T	1900	2000 x 1300 x 1300

DRAAIMACHINES

CNC Carrousel-draaien	Max. diameter [mm]	Diameter klauwplaat [mm]	Hoogte [mm]	Slag [mm]	
STANKO	1.400	1.400	500	700	
Vertimaxx 2000	2.050	1.600	1.450	1.175	
TOSHULIN Basicturn 2000	2.300	2.000	2.000	1.350	Met aangedreven gereedschap
Schiess	2.100	1.600	1.100	775	

CNC Draaien	Diameter boven bed/dwarssupport [mm]	Lengte [mm]	
CTX 510 ECO	465	1.100	Met aangedreven gereedschap
Monforts RNC-7 1500	700	1.500	
CMZ TD35Y-3200	950/550	3.200	Met aangedreven gereedschap, Y-as en meelopende hydraulische bril (slag: 30-245 mm)
PUMA 600M II	1.030/800	1.600	Met aangedreven gereedschap

Teach-In Draaien	Diameter boven bed/dwarssupport [mm]	Lengte [mm]
Weiler E50	530/170	2.000

Conventioneel draaien	Diameter boven bed/dwarssupport [mm]	Lengte [mm]
Boehring	440/170	1.5000

KOTTERMACHINES

	Tafelafmeting [mm]	Verplaatsing (x, y, z) [mm]	
Sacem	1.600 x 2.000 CNC ronddraaitafel	4.000 x 2.000 x 2.000	Spillengte: 1.000 mm

FREESMACHINES

	Tafelafmeting [mm]	Verplaatsing (x, y, z) [mm]	
Hedelius T7 Single	1.900 x 750	1.600 x 750 x 800	5-assig simultaan + CNC draaitafel ø1.100 mm
Hedelius T7 Single	1.900 x 750	1.600 x 750 x 800	5-assig simultaan + CNC draaitafel ø1.100 mm
AXA 4000 XTS 50	4.000 x 1.000	4.000 x 900 x 950	5-assig + CNC draaitafel ø1.200 mm
Anayak Performer 2500	2.700 x 850	2.500 x 1.000 x 1.100	5-assig + CNC draaitafel (opbouw)
Anayak Performer 2000	2.200 x 850	2.000 x 1.000 x 1.100	5-assig + CNC draaitafel (opbouw)
YCM NXV 1020A	1.120 x 520	1.020 x 520 x 540	3-assig

MULTITASK MACHINES

	Diameter boven bed [mm]	Lengte [mm]	
PUMA SMX 3100S	660	1.540	Klauwplaat hoofdspil + overnamespil: 340mm Toerental: 3.000 RPM Vermogen freesspindel: 26kW Freesspindel toerental: 12.000 RPM Volledig 5-assig simultaan

SLIJPMACHINES

Rondslijpen buiten	Diameter [mm]	Lengte [mm]	
Schautd CNC	515	3.000	Max. gewicht 800 kg

Rondslijpen binnen	Diameter [mm]	Lengte [mm]	
Wotan	450	700	

Vlak slijpen	Tafelafmeting [mm]	Lengte [mm]	
Elb	900 x 500	400	

Radiaal slijpen	Diameter [mm]	Lengte [mm]	
Elb	600	250	

Universeel	Diameter [mm]	Lengte [mm]
Kellenberger	500	1.650

CNC ZAAGMACHINE

	Diameter [mm]
KASTO Twin A4 x 5	460

BALANCEREN

	Technische gegevens	Lengte [mm]
Schenk	Max. ϕ 3.500 mm Max. gewicht 1.500 kg Max. toerental 3.600 RPM	3.870

BOREN

	Tafelafmeting [mm]	Hoogte [mm]
Raboma 1250	1.250 x 1.500	1.600
Raboma 1600	1.600 x 1.500	1.600

METEN

	Verplaatsing (x, y, z) [mm]	
Zeiss MC 850	850 x 1.200 x 600	Incl. meetrapportage
Zeiss Spectrum plus 7/10/6	700 x 1.000 x 600	Incl. meetrapportage

WARMTEBEHANDELINGEN

	Afmetingen (L x B x H) [mm]	
Gloeioven	1.600 x 1.600 x 900	Incl. gloeirapportage

WITMETAAL GIETEN

Materiaal:

- WM-90
- Silion